

EVDO Fixed Wireless Phones

- ◆ **CDMA2000 EVDO Rev. A**
- ◆ **Backward compatible to CDMA 2000 EVDO Rev 0**
- ◆ **Backward compatible CDMA 2000 1x RTT, IS-95 A/B**
- ◆ **High Speed Data: 3.1Mbps downlink, 1.8Mbps uplink**
- ◆ **1x RTT packet data**
- ◆ **Voice Codecs: 8k EVRC, 13k QCELP, 4GV**
- ◆ **MIDI-Polyphonic Ring Tones**
- ◆ **Caller ID, Call Waiting, Three-Way Calling**
- ◆ **Speaker Phone**
- ◆ **Big Graphic LCD Display**
- ◆ **USB 2.0 Interface**
- ◆ **Internal Dual-Antenna Receive Diversity**
- ◆ **Built-in Driver and Connection Manager**
- ◆ **OS: Windows 2000, XP, Vista, Windows 7, Linux, Mac**



EVDO Fixed Wireless Phones

Startcom's ET1000 Series EVDO Fixed Wireless Phones offer customers with high quality voice, SMS functions and high speed data service. The high-speed data service enable user to access to internet wirelessly. Call-waiting, forwarding and 3-way calling are also supported. MIDI ring tones enhance the music quality for improved user experiences.

In addition to Startcom's standard products, it also provides customer with customized features, such as language, operator-depend features, casing color options, charger options, etc. Private-labeling is also provided as required by customers.

Specifications

Chipset

- ✧ QSC6085

Internal Memory

- ✧ 128MB NAND+ 64MB DDR

Frequency Band

- ✧ 800MHz (Cellular-Band) : ET1000B
- ✧ 1900MHz (PCS-Band) : ET1000C
- ✧ 800MHz + 1900MHz : ET1000D

Standard Compliances

- ✧ CDMA2000 EVDO Rev. A
- ✧ CDMA2000 1x (backward compatible to IS-95)
- ✧ Backward compatible CDMA 2000 1x RTT, IS-95 A/B

Data Service

- ✧ EVDO Rev.A: 3.1Mbps downlink, 1.8Mbps uplink
- ✧ 1x Packet Data: 1.53.6Kbps

Specifications

- ✧ Operation Temperature: -20 °C ~ 55 °C
- ✧ Storage Temperature : -40 °C ~ 75 °C
- ✧ Operation Humidity : 0% ~ 95%
- ✧ Charger AC Input : 90 ~ 240 VAC, 50~60Hz
- ✧ Charger DC Output : 5VDC @800mA
- ✧ Battery Capacity : 3.6V, 1500mAh, Ni-MH
- ✧ Battery Operation Time: Talk >4hrs / Standby >250hrs
- ✧ Size : 200(L)x175(W)x67(H) mm
- ✧ Weight : < 1.0kg
- ✧ Antenna Conn Type : Dual-Antenna Receive Diversity
Primary Antenna: TNC
Secondary Antenna: Internal

Features

Basic Features

- ✧ Large 128x64 Dot-Matrix Graphic LCD
- ✧ Blue LCD Backlight
- ✧ 25 Keys with On/Off Key
- ✧ Speaker Phone for Ringing and Hand-Free Mode
- ✧ USB2.0 Interface (Maintenance and/or Data)
- ✧ Mechanical Power Switch for Complete Power-Off

Network Dependent Features

- ✧ Call Waiting, Forwarding, 3-Way Calling
- ✧ Caller ID
- ✧ Voice Mail
- ✧ Two-Way SMS Messaging
- ✧ OTA (IS-683 / IS-683A)

User Interface Features

- ✧ 200-Entry Contacts + Contacts in UIM (if used)
- ✧ 200-Items SMSs + SMS in UIM (if used)
- ✧ Call History
- ✧ Calendar, Schedule, Alarm Clock
- ✧ Screen Saver with Date/Time Display
- ✧ Speed-Dialing
- ✧ Polyphonic Ring Tones
- ✧ Lock Cell, Operator, Pin/UIM Card, Keypad

Selectable Features

- ✧ R-UIM or No-UIM
- ✧ Languages : English, Spanish, Chinese, Arabic,
Others can provided as required
- ✧ AC Plug Type for Charger
- ✧ Casing Colors: White, Black, Grey
- ✧ Call Meeting Function (if network supports)